

CLF TOURCASES

- STRONG AND PROFESSIONAL DESIGN
- LIFE TIME WARRANTY UNDER NORMAL USE
- PROTECTION DEGREE IP65
- WORKING TEMPERATURE -40° ~ 90°
- IMPACT CASE RESISTANCE CASE BODY
- ERGONOMIC HANDLE WITH RUBBER COATING



CLF TOURCASE 115



External DIM.(LxWxD) 270 x 231 x 185 mm
 Internal DIM.(LxWxD) 243 x 182 x 157 mm
 Material Engineer Resin+Glass fibre
 Weight 1.4 Kg
 Volume 6.57 L
 Buoyancy MAX. 6.38 Kg
 Supplied with solid cube foam

CLF TOURCASE 130



External DIM.(LxWxD) 308 x 269 x 150 mm
 Internal DIM.(LxWxD) 280 x 200 x 122 mm
 Material Engineer Resin+Glass fibre
 Weight 1.99 Kg
 Volume 6.44 L
 Buoyancy MAX. 6.16 Kg
 Supplied with solid cube foam

CLF TOURCASE 140



External DIM.(LxWxD) 410 x 342 x 204 mm
 Internal DIM.(LxWxD) 380 x 271 x 178.5 mm
 Material Engineer Resin+Glass fibre
 Weight 3.98 Kg
 Volume 17.9 L
 Buoyancy MAX. 17.4 Kg
 Supplied with solid cube foam

CLF TOURCASE 142



External DIM.(LxWxD) 450 x 340 x 160 mm
 Internal DIM.(LxWxD) 430 x 300 x 150 mm
 Material Engineer Resin+Glass fibre
 Weight 2.20 Kg
 Volume 15 L
 Buoyancy MAX. 15 Kg
 Supplied with solid cube foam

CLF TOURCASE 144



External DIM.(LxWxD) 479 x 415 x 150 mm
 Internal DIM.(LxWxD) 448 x 345 x 121 mm
 Material Engineer Resin+Glass fibre
 Weight 4.34 Kg
 Volume 15 L
 Buoyancy MAX. 16,30 Kg
 Supplied with solid cube foam

CLF TOURCASE 146



External DIM.(LxWxD) 479 x 415 x 217 mm
 Internal DIM.(LxWxD) 448 x 345 x 186 mm
 Material Engineer Resin+Glass fibre
 Weight 5,18 Kg
 Volume 28,5 L
 Buoyancy MAX. 26,8 Kg
 Supplied with solid cube foam

CLF TOURCASE 148



External DIM.(LxWxD) 557 x 348 x 248 mm
 Internal DIM.(LxWxD) 521 x 278 x 190.8 mm
 Material Engineer PP with fiberglass
 Weight 7,6 Kg
 Volume 28,5 L
 Buoyancy MAX. 27,4 Kg
 With trolley and wheels
 Perfectly designed as personal tool case
 Possible to choose solid cube foam as interior

CLF TOURCASE 150



External DIM.(LxWxD) 557 x 348 x 199 mm
 Internal DIM.(LxWxD) 526x 275 x 169,5 mm
 Material Engineer Resin+Glass fibre
 Weight 4,98 Kg
 Volume 20,28 L
 Buoyancy MAX. 19,5 Kg

CLF TOURCASE 155



External DIM.(LxWxD) 610 x 472 x 275 mm
 Internal DIM.(LxWxD) 540 x 402 x 250 mm
 Material Engineer Resin+Glass fibre
 Weight 8 Kg
 Volume 73.10 L
 Buoyancy MAX. 73 Kg
 With trolley and wheels

CLF TOURCASE 160



External DIM.(LxWxD) 670 x 508 x 355 mm
 Internal DIM.(LxWxD) 584 x 442 x 329 mm
 Material Engineer PP with Glass fibre
 Weight 10,92 Kg
 Volume 82,21 L
 Buoyancy MAX. 83,2 Kg
 With trolley and wheels

CLF TOURCASE 170



External DIM.(LxWxD) 851 x 556 x 429 mm
 Internal DIM.(LxWxD) 763 x 483 x 402 mm
 Material Engineer Resin with fiberglass
 Weight 16,67 Kg
 Volume 145,84 L
 Buoyancy MAX. 143 Kg
 With trolley and wheels