

NEW


RDMNODE

The **RdmNode** is a 4-port eDMX node that converts Art-Net and sACN to DMX-512 and vice versa. This Ethernet node comes in a DIN rail form factor that is ideal for system integration and architectural lighting projects.

This RdmNode is a jack of all trades in DMX data conversion. This versatile device features an intuitive drag & drop web interface for configuring data routing, merging processes and port settings. Presets with the most common conversions are just a click away.

When paired with the CueCore3, 4 additional universes are unlocked. Maximum 8 RdmNodes can be paired per CueCore3 to output 32 universes in total.

As a state-of-the-art component in your DMX infrastructure, the RdmNode – pending a firmware upgrade – transfers fixture data back and forth using the RDM over Art-Net protocol.

SPECIFICATIONS



- 4 ports
- 4 x DMX 512 control
- Art-Net and sACN to DMX
- 100Mbps Ethernet port
- RDM over Art-net
- web-based user interface
- PoE powered
- DIN-rail form factor
- 5 year warranty



SPINODE

The **SpiNode** is a high-performance eDMX node designed for LED pixel control. It translates Art-Net and sACN into 4 independent SPI outputs, each capable of driving up to 1,024 pixels with a maximum of 6 DMX universes per port. The total system capacity reaches 24 DMX universes across all outputs.

The SpiNode supports a wide range of SPI protocols, including WS2812, SK6812, APA102, WS2811, and many others

The **SpiNode** features a web-based interface that provides an intuitive and user-friendly configuration environment. Built-in test functions assist with system setup by identifying universe boundaries, mapping individual LEDs for easy configuration, and detecting faulty LEDs for troubleshooting.

When paired with the CueCore3, 16 additional universes are unlocked. Maximum 2 SpiNodes can be paired per CueCore3 to obtain 32 universes in total.

SPECIFICATIONS



- 4 SPI ports
- 4 x 1,024 RGB pixel control
- Art-Net and sACN to SPI
- 100Mbps Ethernet port
- web-based user interface
- PoE powered
- DIN-rail form factor
- 5 year warranty

